



European Technical Assessment

ETA-20/0471
dated 27/05/2020

English translation prepared by CSTB - Original version in French language

General Part

Nom commercial:
Trade name

SITA Acciaio CE 1 TTSC

Famille de produit:
Product family

Cheville métallique à expansion par vissage à couple contrôlé, de fixation dans le béton fissuré et non fissuré diamètres M8, M10, M12 et M16

Torque-controlled expansion anchor for use in cracked and uncracked concrete: sizes M8, M10, M12 and M16

Titulaire:
Manufacturer

G&B Fissaggi S.r.l.
Corso Savona, 22
10029 Villastellone (TO)
Italy

Usine de fabrication:
Manufacturing plants

G&B Fissaggi Plant B

Cette évaluation contient:
This Assessment contains

13 pages incluant 10 pages d'annexes qui font partie intégrante de cette évaluation
13 pages including 10 pages of annexes which form an integral part of this assessment

Base de l'ETE:
Basis of ETA

EAD 330232-00-0601, "Ancrages mécaniques dans le béton"
EAD 330232-00-0601, "Mechanical fasteners for use in concrete"

Cette évaluation remplace:
This Assessment replaces

-

Specific Part

1 Technical description of the product

The SITA Acciaio CE 1 TTSC is an anchor made of zinc electroplated steel which is placed into a drilled hole and anchored by torque-controlled expansion.

The anchor is placed into a drilled hole and anchored by torque-controlled expansion.

The illustration and the description of the product are given in Annexes A.

2 Specification of the intended use

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annexes B.

The provisions made in this European technical assessment are based on an assumed working life of the anchor of 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic tension resistance	See Annex C1
Characteristic shear resistance	See Annex C2
Displacements	See Annex C5
Characteristic resistance under seismic action	See Annex C6

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Characteristic tension resistance under fire	See Annex C3
Characteristic shear resistance under fire	See Annex C4

3.3 Hygiene, health and the environment (BWR 3)

Regarding dangerous substances contained in this European technical approval, there may be requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provisions of the Construction Products Directive, these requirements need also to be complied with, when and where they apply.

3.4 Safety in use (BWR 4)

For Basic requirement Safety in use the same criteria are valid as for Basic Requirement Mechanical resistance and stability.

3.5 Protection against noise (BWR 5)

Not relevant.

3.6 Energy economy and heat retention (BWR 6)

Not relevant.

3.7 Sustainable use of natural resources (BWR 7)

For the sustainable use of natural resources no performance was determined for this product.

3.8 General aspects relating to fitness for use

Durability and Serviceability are only ensured if the specifications of intended use according to Annex B1 are kept.

4 Assessment and verification of constancy of performance (AVCP)

According to the Decision 96/582/EC of the European Commission¹, as amended, the system of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) given in the following table apply.

Product	Intended use	Level or class	System
Metal anchors for use in concrete	For fixing and/or supporting to concrete, structural elements (which contributes to the stability of the works) or heavy units	—	1

5 Technical details necessary for the implementation of the AVCP system

Technical details necessary for the implementation of the Assessment and verification of constancy of performance (AVCP) system are laid down in the control plan deposited at Centre Scientifique et Technique du Bâtiment.

The manufacturer shall, on the basis of a contract, involve a notified body approved in the field of anchors for issuing the certificate of conformity CE based on the control plan.

The original French version is signed by

La cheffe de division, Anca CRONOPOL

¹ Official Journal of the European Communities L 254 of 08.10.1996

Hex head version:



Marking on the bolt:

MX/L, where:


MX = thread diameter

L = total length

Marking on the clip:

S1C

Intended use:



Intended use:

Use in cracked or uncracked concrete in dry internal conditions

SITA Acciaio CE 1 TTSC

Annex A1

Product description
Installation conditions

Different parts of the anchor:




Table 1: Materials

Part	Designation	Material	Protection
1	Thread bolt	Coldform steel, grade C-1035	Zinc plated 5 μ m
2	Expansion clip	Stainless steel	-
3	Washer	DIN 125 or EN ISO 7089 DIN 9021 or DIN 440 or D IN EN ISO 7093	Zinc plated
4	Hexagonal nut	DIN 934 Grade 8 acc. to DIN 267-4	Zinc plated

SITA Acciaio CE 1 TTSC

Annex A2

Product description

Material

Specifications of intended use

Anchorage subject to:

- Static, quasi-static and fire
- Seismic action for performance category C1.

Base materials:

- Cracked concrete and non-cracked concrete
- Reinforced or unreinforced normal weight concrete of strength classes C 20/25 at least to C50/60 at most according to EN 206: 2000-12.

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions.

Design:

- The anchorages are designed in accordance with the ETAG001 Annex C "Design Method for Anchorages" or CEN/TS 1992-4-4 "Design of fastenings for use in concrete" under the responsibility of an engineer experienced in anchorages and concrete work.
- For application with resistance under fire exposure the anchorages are designed in accordance with method given in TR020 "Evaluation of Anchorage in Concrete concerning Resistance to Fire".
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings.

Installation:

- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site.
- Use of the anchor only as supplied by the manufacturer without exchanging the components of an anchor.
- Anchor installation in accordance with the manufacturer's specifications and drawings and using the appropriate tools.
- Effective anchorage depth, edge distances and spacing not less than the specified values without minus tolerances.
- Hole drilling by hammer drill.
- Cleaning of the hole of drilling dust.
- Application of specified torque moment using a calibrated torque wrench.
- In case of aborted hole, drilling of new hole at a minimum distance of twice the depth of the aborted hole, or smaller distance provided the aborted drill hole is filled with high strength mortar and no shear or oblique tension loads in the direction of aborted hole.

SITA Acciaio CE 1 TTSC

Annex B1

Intended Use
Specifications

Table 2: Anchor dimensions

				M8	M10	M12	M16
Length of the anchor	Min.	L	[mm]	60	85	90	115
	Max.		[mm]	240	220	220	220
Fixture thickness	Min.	t _{fix}	[mm]	1	1	1	1
	Max.		[mm]	185	140	130	100
Length expansion sleeve		l _{clip}	[mm]	14	18	22	26
Width torque wrench		SW	[mm]	13	17	19	24

Table 3: Installation data

				M8	M10	M12	M16
Drill hole diameter	d _{cut}	[mm]		≤ 8,45	≤ 10,45	≤ 12,5	≤ 16,5
Drill hole depth	h ₁	[mm]		55	75	75	100
Embedment depth	h _{ef}	[mm]		40	60	60	80
Installation torque	T _{inst}	[Nm]		30	50	70	130
Diameter through hole fixture	d _f	[mm]		9	12	14	18
Min. member thickness	h _{min}	[mm]		100	120	120	160
Minimum edge distance	c _{min}	[mm]		65	60	80	85
Minimum spacing	s _{min}	[mm]		65	150	80	85

SITA Acciaio CE 1 TTSC

Intended Use
 Installation parameters

Annex B2

Table 4: Characteristic values for tension loads in case of static and quasi static loading for design method A

			M8	M10	M12	M16	
Steel failure							
Char. resistance	$N_{Rk,s}$	[kN]	22,2	31,6	43,4	75,4	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,88				
Pullout failure $N_{Rk,p} = \Psi_c \times N_{Rk,p}^0$							
Char. resistance in concrete C20/25	cracked	$N_{Rk,p}^0$	[kN]	3	9	12	12
	non-cracked	$N_{Rk,p}^0$	[kN]	6	12	12	35
Partial safety factor for cracked or non-cracked concrete		$\gamma_2 = \gamma_{inst}$	[-]	1,2		1,4	
Increasing factor for N_{RK}	concrete C30/37	Ψ_c	[-]	1,22			
	concrete C40/50		[-]	1,41			
	concrete C50/60		[-]	1,55			
Concrete cone failure and splitting failure							
Effective embedment depth	h_{ef}	[mm]	40	60	60	80	
Factor for determination of the resistance to concrete cone failure	$k_1 = k_{cr}$	[-]	Values are given in TR055 depending of the design guide				
	$k_1 = k_{ucr}$	[-]					
Partial safety factor for cracked or non-cracked concrete		$\gamma_2 = \gamma_{inst}$	[-]	1,2		1,4	
Increasing factor for N_{RK}	concrete C30/37	Ψ_c	[-]	1,22			
	concrete C40/50		[-]	1,41			
	concrete C50/60		[-]	1,55			
Char. spacing	concrete cone failure	$S_{cr,N}$	[mm]	120	180	180	240
	splitting failure	$S_{cr,sp}$	[mm]	200	300	360	400
Char. edge distance	concrete cone failure	$C_{cr,N}$	[mm]	60	90	90	120
	splitting failure	$C_{cr,sp}$	[mm]	100	150	180	200

¹⁾ In absence of other national regulations

SITA Acciaio CE 1 TTSC

Annex C1

Design according to Technical Report TR055
Characteristic resistance under tension loads

Table 5: Characteristic values for shear loads in case of static and quasi static loading for design method A

			M8	M10	M12	M16
Steel failure without lever arm						
Char. resistance	$V_{Rk,s}$	[kN]	8,1	17,6	24,7	45,9
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25			
Steel failure with lever arm						
Char. bending resistance	$M^0_{Rk,s}$	[Nm]	22,8	45,5	76,6	194,8
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25			
Concrete pry-out failure						
Factor for determination of resistance to pry-out failure	$k_3=k_8$	[-]	1,0	2,0	2,0	2,0
Partial safety factor	$\gamma_2 = \gamma_{inst}^{1)}$	[-]	1,0			
Concrete edge failure						
Effective length of anchor under shear loading	l_f	[mm]	40	60	60	80
Outside diameter of anchor	d_{nom}	[mm]	8	10	12	16
Partial safety factor	$\gamma_2 = \gamma_{inst}^{1)}$	[-]	1,0			

¹⁾ In absence of other national regulations

SITA Acciaio CE 1 TTSC

Design according to Technical Report TR055
 Characteristic resistance under shear loads

Annex C2

Table 6: Characteristic tension resistance in cracked and non-cracked concrete under fire exposure for design method A acc. TR020

			M8	M10	M12	M16
Steel failure						
Characteristic resistance	R30 $N_{Rk,s,fi}$	[kN]	0,4	0,9	1,7	3,1
	R60 $N_{Rk,s,fi}$	[kN]	0,3	0,8	1,3	2,4
	R90 $N_{Rk,s,fi}$	[kN]	0,3	0,6	1,1	2,0
	R120 $N_{Rk,s,fi}$	[kN]	0,2	0,5	0,8	1,6
Pullout failure (cracked and non-cracked concrete)						
Char. resistance in concrete \geq C20/25	R30 $N_{Rk,p,fi}$	[kN]	0,8	2,3	3,0	4,0
	R60 $N_{Rk,p,fi}$	[kN]	0,8	2,3	3,0	4,0
	R90 $N_{Rk,p,fi}$	[kN]	0,8	2,3	3,0	4,0
	R120 $N_{Rk,p,fi}$	[kN]	0,6	1,8	2,4	3,2
Concrete cone and splitting failure²⁾ (cracked and non-cracked concrete)						
Char. resistance in concrete \geq C20/25	R30 $N_{Rk,c,fi}^0$	[kN]	1,8	5,0	5,0	10,3
	R60 $N_{Rk,c,fi}^0$	[kN]	1,8	5,0	5,0	10,3
	R90 $N_{Rk,c,fi}^0$	[kN]	1,8	5,0	5,0	10,3
	R120 $N_{Rk,c,fi}^0$	[kN]	1,5	4,0	4,0	8,2
Characteristic spacing	$S_{cr,N,fi}$	[mm]	160	240	240	320
Characteristic edge distance	$C_{cr,N,fi}$	[mm]	80	120	120	160

¹⁾ Design under fire exposure is performed according to the design method given in TR 020. Under fire exposure usually cracked concrete is assumed. The design equations are given in TR 020, Section 2.2.1.

²⁾ As a rule, splitting failure can be neglected when cracked concrete and reinforcement is assumed.

TR 020 covers design for fire exposure from one side. For fire attack from more than one side the edge distance must be increased to $c_{min} \geq 300$ mm and $\geq 2 \cdot h_{ef}$.

In absence of national regulation, the partial safety factor $\gamma_{Ms} = 1,0$ is recommended in fire situation

SITA Acciaio CE 1 TTSC

Design according to Technical Report TR020
Characteristic tension resistance under fire exposure

Annex C3

Table 7: Characteristic shear resistance in cracked and non-cracked concrete under fire exposure for design method A acc. TR020

			M8	M10	M12	M16
Steel failure without lever arm						
Characteristic resistance	R30 $V_{Rk,s,fi}$	[kN]	0,4	0,9	1,7	3,1
	R60 $V_{Rk,s,fi}$	[kN]	0,3	0,8	1,3	2,4
	R90 $V_{Rk,s,fi}$	[kN]	0,3	0,6	1,1	2,0
	R120 $V_{Rk,s,fi}$	[kN]	0,2	0,5	0,8	1,6
Steel failure with lever arm						
Characteristic bending moment	R30 $M^0_{Rk,s,fi}$	[Nm]	0,4	1,1	2,6	6,7
	R60 $M^0_{Rk,s,fi}$	[Nm]	0,3	1,0	2,0	5,0
	R90 $M^0_{Rk,s,fi}$	[Nm]	0,3	0,7	1,7	4,3
	R120 $M^0_{Rk,s,fi}$	[Nm]	0,2	0,6	1,3	3,3
Concrete pry-out failure						
Factor for determination of resistance to pry-out failure	$k_3=k_8$	[-]	1,0	2,0	2,0	2,0
Characteristic resistance	R30 $V_{Rk,cp,fi}$	[kN]	1,8	10,0	10,0	20,6
	R60 $V_{Rk,cp,fi}$	[kN]	1,8	10,0	10,0	20,6
	R90 $V_{Rk,cp,fi}$	[kN]	1,8	10,0	10,0	20,6
	R120 $V_{Rk,cp,fi}$	[kN]	1,5	8,0	8,0	16,5
Concrete edge failure						
Eff. length of anchor under shear loading	l_f	[mm]	40	60	60	80
Outside diameter of anchor	d_{nom}	[mm]	8	10	12	16

1) Design under fire exposure is performed according to the design method given in TR 020. Under fire exposure usually cracked concrete is assumed. The design equations are given in TR 020, Section 2.2.2.

TR 020 covers design for fire exposure from one side. For fire attack from more than one side the edge distance must be increased to $c_{min} \geq 300$ mm and $\geq 2 \cdot h_{ef}$.

SITA Acciaio CE 1 TTSC

Annex C4

Design according to Technical Report TR020
 Characteristic tension resistance under fire exposure

Table 8: Displacements under tension loading

		M8	M10	M12	M16
Tension load in non-cracked concrete C20/25 [kN]		2,38	4,76	5,44	11,90
Displacement	δ_{N0} [mm]	0,05	0,10	0,06	0,30
	$\delta_{N\infty}$ [mm]	0,65	1,17	1,53	0,65
Tension load in non-cracked concrete C50/60 [kN]		3,69	9,92	10,20	18,45
Displacement	δ_{N0} [mm]	0,05	0,24	0,10	0,10
	$\delta_{N\infty}$ [mm]	0,65	1,17	1,53	0,65
Tension load in cracked concrete C20/25 [kN]		1,19	4,76	4,08	4,08
Displacement	δ_{N0} [mm]	0,05	0,83	1,04	0,40
	$\delta_{N\infty}$ [mm]	1,15	1,17	1,53	1,14
Tension load in cracked concrete C50/60 [kN]		1,85	4,76	10,20	6,33
Displacement	δ_{N0} [mm]	2,95	0,94	1,89	3,43
	$\delta_{N\infty}$ [mm]	2,95	1,17	1,53	3,43

Tableau 9: Displacements under shear loading

		M8	M10	M12	M16
Shear load in cracked and non-cracked concrete C20/25 to C50/60 [kN]		4,63	9,14	9,52	26,23
Displacement	δ_{V0} [mm]	5,50	5,26	5,84	3,60
	$\delta_{V\infty}$ [mm]	8,25	7,89	8,76	5,40

Additional displacement due to anular gap between anchor and fixture is to be taken into account.

SITA Acciaio CE 1 TTSC

Displacements

Annex C5

Table 10: Characteristic values of resistance under tension loads in case of seismic performance category C1 for design acc. to TR045

			M12	M16
Steel failure				
Char. resistance	$N_{Rk,s,seis}$	[kN]	43,4	75,4
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,88 ¹⁾	
Pullout failure				
Characteristic resistance	$N_{Rk,p,seis}$	[kN]	12	12
Partial safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,4	

¹⁾ In absence of other national regulations

Table 11: Characteristic values of resistance under shear loads in case of seismic performance category C1 for design acc. to TR045

			M12	M16
Steel failure without lever arm				
Characteristic resistance	$V_{Rk,s,seis}$	[kN]	13,6	24,8
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,25 ¹⁾	

¹⁾ In absence of other national regulations

SITA Acciaio CE 1 TTSC

Performances

Characteristic resistance under seismic actions
 Design according to TR045

Annex C6