

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments

★ ★ ★
★ Designated
according to
Article 29 of Regula-
tion (EU) No 305/2011
and member of EOTA
(European Organi-
sation for Technical
Assessment)
★ ★ ★
★ ★

European Technical Assessment

ETA-99/0010
of 23 July 2018

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Trade name of the construction product

Product family
to which the construction product belongs

Manufacturer

Manufacturing plant

This European Technical Assessment
contains

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

This version replaces

Deutsches Institut für Bautechnik

Wedge anchor BZ plus and BZ-IG

Torque controlled expansion fastener
for use in concrete

MKT
Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach

MKT
Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach

36 pages including 3 annexes which form an integral part
of this assessment

EAD 330232-00-0601

ETA-99/0010 issued on 6 April 2016

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific Part**1 Technical description of the product**

The Wedge anchor BZ plus and BZ-IG is an fastener made of zinc plated steel, stainless steel or high corrosion resistant steel which is placed into a drilled hole and anchored by torque-controlled expansion. The following fastener types are covered:

- Fastener type BZ plus with external thread, washer and hexagon nut, sizes M8 to M27,
- Fastener type BZ-IG S with internal thread, hexagon head nut and washer S-IG, sizes M6 to M12,
- Fastener type BZ-IG SK with internal thread, countersunk head screw and countersunk washer SK-IG, sizes M6 to M12,
- Fastener type BZ-IG B with internal thread, hexagon nut and washer MU-IG, sizes M6 to M12.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the fastener is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fastener of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment**3.1 Mechanical resistance and stability (BWR 1)**

Essential characteristic	Performance
Characteristic values for static and quasi static action	for BZ plus see Annex C1 to C5 for BZ-IG see Annex C11 to C13
Displacements	for BZ plus see Annex C9 to C10 for BZ-IG see Annex C15
Characteristic values for seismic performance categories C1 and C2	for BZ plus see Annex C6

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	for BZ plus see Annex C7 and C8 for BZ-IG see Annex C14

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 330232-00-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.




Issued in Berlin on 23 July 2018 by Deutsches Institut für Bautechnik

Dr.-Ing. Lars Eckfeldt
p. p. Head of Department

beglaubigt:
Lange

Fastener version	Product description	Intended use	Performance
BZ plus	Annex A1 - Annex A4	Annex B1 – Annex B7	Annex C1 – Annex C10
BZ-IG	Annex A1 Annex A5 – Annex A7	Anhang B1 – Anhang B2 Anhang B8 – Anhang B10	Anhang C11 – Anhang C15

Wedge anchor BZ plus



Wedge anchor BZ-IG M6 to M12

Fastener system


BZ-IG S		Washer	Hexagon head screw
BZ-IG SK	Conical bolt Expansion sleeve	Countersunk washer	Countersunk head screw
BZ-IG B		Washer Hexagon nut	Commercial standard rod

Wedge Anchor BZ plus and BZ-IG

Product description
Fastener types


Annex A1

Intended use Wedge Anchor BZ plus



Fastener size BZ plus M8 to M20:


Marking 1 e.g.: $\diamond BZ 15/35$



Marking 1 e.g.: $\diamond BZ 15/35$

- \diamond identifying mark of manufacturing plant
- BZ fastener identity
- 15 max. thickness of fixture for h_{ef}
- 35 max. thickness of fixture for $h_{ef,red}$
- M8 thread diameter
- Additional marking:
- A4 stainless steel
- HCR high corrosion resistant steel


Marking 2 e.g.: $\diamond BZ 15$



Marking 2 e.g.: $\diamond BZ 15$

- \diamond identifying mark of manufacturing plant
- BZ fastener identity
- 15 maximum thickness of fixture for h_{ef}
- M8 thread diameter
- Additional marking:
- A4 stainless steel
- HCR high corrosion resistant steel

Fastener size BZ plus M24 and M27:




Marking 3 e.g.: $\diamond BZ M24-30$

- \diamond identifying mark of manufacturing plant
- BZ fastener identity
- M24 thread diameter
- 30 maximum thickness of fixture
- Additional marking:
- A4 stainless steel
- HCR high corrosion resistant steel

Marking of length	C (c)	D (d)	E (e)	F (f)	G (g)	H (h)	I (i)	J (j)	K (k)	L (l)	M (m)	N (n)
Length of fastener min \geq	63,5	76,2	88,9	101,6	114,3	127,0	139,7	152,4	165,1	177,8	190,5	203,2
Length of fastener max <	76,2	88,9	101,6	114,3	127,0	139,7	152,4	165,1	177,8	190,5	203,2	215,9

Marking of length	O (o)	P (p)	Q (q)	R (r)	S (s)	T (t)	U (u)	V (v)	W (w)	X (x)	Y (y)	Z (z)
Length of fastener min \geq	215,9	228,6	241,3	254,0	279,4	304,8	330,2	355,6	381,0	406,4	431,8	457,2
Length of fastener max <	228,6	241,3	254,0	279,4	304,8	330,2	355,6	381,0	406,4	431,8	457,2	483,0

Filling washer and reducing adapter for filling the annular gap between fastener and fixture



Wedge anchor BZ plus

Product description

Fastener sizes and marking

Annex A3

Table A1: Fastener dimensions BZ plus

Fastener size		M8	M10	M12	M16	M20	M24	M27
Conical bolt	Thread	M8	M10	M12	M16	M20	M24	M27
	$\emptyset d_k =$	7,9	9,8	12,0	15,7	19,7	24	28
Length of fastener ¹⁾	Steel, zinc plated	L	$65 + t_{fix}$	$80 + t_{fix}$	$96,5 + t_{fix}$	$118 + t_{fix}$	$137 + t_{fix}$	$161 + t_{fix}$
	A4, HCR	L	$65 + t_{fix}$	$80 + t_{fix}$	$96,5 + t_{fix}$	$118 + t_{fix}$	$137 + t_{fix}$	$168 + t_{fix}$
	reduced anchorage depth	$L_{hef,red}$	$54 + t_{fix}$	$60 + t_{fix}$	$76,5 + t_{fix}$	$98 + t_{fix}$	-	-
Hexagon nut	SW	13	17	19	24	30	36	41

¹⁾ With additional use of filling washer 3b the usable thickness of fixture will reduce 5mm

Dimensions in mm

Table A2: Materials BZ plus

No.	Part	BZ plus		BZ plus A4	BZ plus HCR
		Steel, zinc plated		Stainless steel A4	High corrosion resistant steel (HCR)
		galvanized $\geq 5\mu m$	sherardized $\geq 40\mu m$		
1	Conical bolt	M8 to M20: Cold formed or machined steel, galvanized, cone plastic coated	M8 to M20: Cold formed or machined steel, sherardized, cone plastic coated	M8 to M20: Stainless steel (e.g. 1.4401, 1.4404, 1.4578, 1.4571) EN 10088:2014, cone plastic coated	M8 to M20: High corrosion resistant steel 1.4529 or 1.4565, EN 10088:2014, cone plastic coated
	Threaded bolt	M24 and M27: Steel, galvanized	M24 and M27: steel, sherardized	M24: Stainless steel (e.g. 1.4401, 1.4404) EN 10088:2014	M24: High corrosion resistant steel 1.4529 or 1.4565, EN 10088:2014
	Threaded cone		M24 and M27: Steel, galvanized		
2	Expansion sleeve	M8 to M20: Steel (e.g. 1.4301 or 1.4401) EN 10088:2014,	M8 to M20: Steel (e.g. 1.4301 or 1.4401) EN 10088:2014,	Stainless steel (e.g. 1.4401, 1.4404, 1.4571) EN 10088:2014	Stainless steel (e.g. 1.4401, 1.4404, 1.4571) EN 10088:2014
		M24 and M27: Steel acc. to EN 10139:1997	M24 and M27: Steel acc. to EN 10139:1997		
3a	Washer	Steel, galvanized	Steel, zinc plated	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014	High corrosion resistant steel 1.4529 or 1.4565, EN 10088:2014
3b	Filling washer				
4	Hexagon nut	Steel, galvanized, coated	Steel, zinc plated	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014, coated	High corrosion resistant steel 1.4529 or 1.4565, EN 10088:2014, coated

Wedge anchor BZ plus

Product description

Dimensions and materials

Annex A4




English translation prepared by DIBt

Intended use Wedge anchor BZ-IG

Pre-setting installation (V)	Through-setting installation (D)
Pre-set fastener body, the fixture bears on the screw or thread rod only	The fastener is set through the fixture, the fixture bears on the conical bolt BZ-IG
BZ-IG S consisting of BZ-IG and S-IG	
BZ-IG SK consisting of BZ-IG and SK-IG	
BZ-IG B consisting of BZ-IG and MU-IG	
Setting tool	
BZ-IGS M8 V, BZ-IGS M10 V, BZ-IGS M12 V or BZ-IGS M16 V	
BZ-IGS M8 D, BZ-IGS M10 D, BZ-IGS M12 D or BZ-IGS M16 D	
Wedge anchor BZ-IG	
Product description Installation situation BZ-IG	Annex A5

Marking: ◇ identifying mark of manufacturing plant
 BZ fastener identity
 M6 size of internal thread
 10 max. thickness of fixture
 (only Through-setting installation)
Additional marking:
 A4 stainless steel
 HCR high corrosion resistant steel

e.g.: ◇ BZ M6-10 A4



Commercial
standard rod





Table A3: Fastener dimensions BZ-IG

No.	Fastener size	M6	M8	M10	M12
1	Conical bolt with internal thread	Ø dk	7,9	9,8	11,8
	Pre-setting installation	L	50	62	70
	Through-setting installation	L	50 + t _{fix}	62 + t _{fix}	70 + t _{fix}
2	Expansion sleeve			see table A4	
3	Washer			see table A4	
4	Hexagon head screw	width across flats	10	13	17
	Pre-setting installation	L _s	t _{fix} + (13 to 21)	t _{fix} + (17 to 23)	t _{fix} + (21 to 25)
	Through-setting installation	L _s	14 to 20	18 to 22	20 to 22
5	Countersunk washer	Ø countersunk	17,3	21,5	25,9
		t	3,9	5,0	5,7
6	Countersunk head screw	bit size	Torx T30	Torx T45 (Steel, zinc plated) T40 (Stainless steel A4, HCR)	Hexagon socket 6 mm Hexagon socket 8 mm
	Pre-setting installation	L _{sk}	t _{fix} + (11 to 19)	t _{fix} + (15 to 21)	t _{fix} + (19 to 23)
	Through-setting installation	L _{sk}	16 to 20	20 to 25	25
7	Hexagon nut	width across flats	10	13	17
8	Commercial standard rod ¹⁾	type V	L _B ≥	t _{fix} + 21	t _{fix} + 28
		type D	L _B ≥	21	28
¹⁾ acc. to specifications (Table A4)					Dimensions in mm

Wedge anchor BZ-IG

Product description

Fastener parts, marking and dimensions **BZ-IG**

Annex A6

Table A4: Materials BZ-IG

No.	Part	BZ-IG	BZ-IG A4	BZ-IG HCR
		Steel, galvanized ≥ 5 µm acc. to EN ISO 4042:1999	Stainless steel A4	High corrosion resistant steel HCR
1	Conical bolt BZ-IG with internal thread	Machined steel, Cone plastic coated	Stainless steel (e.g. 1.4401, 1.4404, 1.4571, 1.4362) EN 10088:2014, Cone plastic coated	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, Cone plastic coated
2	Expansion sleeve BZ-IG	Stainless steel (e.g. 1.4301, 1.4401) EN 10088:2014	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014
3	Washer S-IG / MU-IG	Steel, galvanized	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014
4	Hexagon head screw S-IG	Steel, galvanized, coated	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014, coated	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, coated
5	Countersunk washer SK-IG	Steel, galvanized	Stainless steel (e.g. 1.4401, 1.4404, 1.4571) EN 10088:2014, zinc plated, coated	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, zinc plated, coated
6	Countersunk head screw SK-IG	Steel, galvanized coated	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014, coated	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, coated
7	Hexagon nut MU-IG	Steel, galvanized coated	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014, coated	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, coated
8	Commercial standard rod	Property class 8.8, EN ISO 898-1:2013 $A_5 > 8\%$ ductile	Stainless steel (e.g. 1.4401, 1.4571) EN 10088:2014, property class 70, EN ISO 3506:2009	High corrosion resistant steel, 1.4529, 1.4565, EN 10088:2014, property class 70, EN ISO 3506:2009

Wedge anchor BZ-IG

Product description
Materials **BZ-IG**

Annex A7

Specifications of intended use

Wedge Anchor BZ plus	M8	M10	M12	M16	M20	M24	M27
Standard anchorage depth							
Steel, galvanized				✓			
Steel, sherardized				✓			
Stainless steel A4 and high corrosion resistant steel HCR			✓				-
Static or quasi-static action			✓				
Fire exposure			✓				
Seismic action (C1 and C2) ¹⁾			✓		-	-	-
Reduced anchorage depth ¹⁾	M8	M10	M12	M16			
Steel, galvanized			✓				
Steel, sherardized			✓				
Stainless steel A4 and high corrosion resistant steel HCR			✓				
Static or quasi-static action			✓				
Fire exposure			✓				
Seismic action (C1 and C2)			-				

¹⁾ only cold formed anchors acc. to Annex A3

Wedge Anchor BZ-IG	M6	M8	M10	M12
Steel, galvanized		✓		
Stainless steel A4 and high corrosion resistant steel HCR		✓		
Static or quasi-static action		✓		
Fire exposure		✓		
Seismic action (C1 and C2)		-		

Base materials:

- Compacted, reinforced or unreinforced normal weight concrete (without fibers) according to EN 206:2013
- Strength classes C20/25 to C50/60 according to EN 206:2013
- Cracked or uncracked concrete

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (steel zinc plated, stainless steel or high corrosion resistant steel).
- Structures subject to external atmospheric exposure including industrial and marine environment or exposure to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel or high corrosion resistant steel).
- Structures subject to external atmospheric exposure and to permanently damp internal condition, if other particular aggressive conditions (high corrosion resistant steel)

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used.)

Wedge Anchor BZ plus and BZ-IG

Intended use
Specifications

Annex B1

Specifications of intended use

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.).
- Dimensioning of fasteners under static or quasi-static action, seismic action or fire exposure according to FprEN 1992-4: 2016 in conjunction with TR 055

Installation:


- Fastener installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Hole drilling by hammer drill bit or vacuum drill bit
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener
- Optionally, the annular gap between fixture and stud of the BZ plus can be filled to reduce the hole. For this purpose, the filling washer (3b) must be used in addition to the supplied washer (3a). For filling use high-strength mortar with compressive strength $\geq 50\text{N/mm}^2$ (VMZ, VMU plus or VMH)
- In case of aborted hole: new drilling at a minimum distance away of twice the depth of the aborted hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application

Wedge Anchor BZ plus and BZ-IG	
---------------------------------------	--

Intended use Specifications	Annex B2
---------------------------------------	-----------------

Table B1: Installation parameters, BZ plus

Fastener size		M8	M10	M12	M16	M20	M24	M27
Nominal drill hole diameter	d_0 [mm]	8	10	12	16	20	24	28
Cutting diameter of drill bit	$d_{cut} \leq$ [mm]	8,45	10,45	12,5	16,5	20,55	24,55	28,55
Installation torque	Steel, galvanized	T_{inst} [Nm]	20	25	45	90	160	200
	Steel, sherardized	T_{inst} [Nm]	16	22	40	90	160	260
	Stainless steel A4, HCR	T_{inst} [Nm]	20	35	50	110	200	290
Diameter of clearance hole in the fixture	$d_f \leq$ [mm]	9	12	14	18	22	26	30
Standard anchorage depth								
Depth of drill hole	Steel, zinc plated	$h_1 \geq$ [mm]	60	75	90	110	125	145
	Stainless steel A4, HCR	$h_1 \geq$ [mm]	60	75	90	110	125	155
Effective anchorage depth	Steel, zinc plated	h_{ef} [mm]	46	60	70	85	100	115
	Stainless steel A4, HCR	h_{ef} [mm]	46	60	70	85	100	125
Reduced anchorage depth								
Depth of drill hole		$h_{1,red} \geq$ [mm]	49	55	70	90	-	-
Reduced effective anchorage depth		$h_{ef,red}$ [mm]	35	40	50	65	-	-



Wedge anchor BZ plus

Intended use
Installation parameters

Annex B3

Table B2: Minimum spacings and edge distances, standard anchorage depth, BZ plus

Fastener size	M8	M10	M12	M16	M20	M24	M27	
Standard thickness of concrete member								
Steel zinc plated								
Standard thickness of member	$h_{min,1}$ [mm]	100	120	140	170	200	230	250
Cracked concrete								
Minimum spacing	s_{min} [mm]	40	45	60	60	95	100	125
	für $c \geq$ [mm]	70	70	100	100	150	180	300
Minimum edge distance	c_{min} [mm]	40	45	60	60	95	100	180
	für $s \geq$ [mm]	80	90	140	180	200	220	540
Uncracked concrete								
Minimum spacing	s_{min} [mm]	40	45	60	65	90	100	125
	für $c \geq$ [mm]	80	70	120	120	180	180	300
Minimum edge distance	c_{min} [mm]	50	50	75	80	130	100	180
	für $s \geq$ [mm]	100	100	150	150	240	220	540
Stainless steel A4, HCR								
Standard thickness of member	$h_{min,1}$ [mm]	100	120	140	160	200	250	-
Cracked concrete								
Minimum spacing	s_{min} [mm]	40	50	60	60	95	125	-
	für $c \geq$ [mm]	70	75	100	100	150	125	
Minimum edge distance	c_{min} [mm]	40	55	60	60	95	125	-
	für $s \geq$ [mm]	80	90	140	180	200	125	
Uncracked concrete								
Minimum spacing	s_{min} [mm]	40	50	60	65	90	125	-
	für $c \geq$ [mm]	80	75	120	120	180	125	
Minimum edge distance	c_{min} [mm]	50	60	75	80	130	125	-
	für $s \geq$ [mm]	100	120	150	150	240	125	
Minimum thickness of concrete member								
Steel zinc plated, stainless steel A4, HCR								
Minimum thickness of member	$h_{min,2}$ [mm]	80	100	120	140	-	-	-
Cracked concrete								
Minimum spacing	s_{min} [mm]	40	45	60	70	-	-	-
	für $c \geq$ [mm]	70	90	100	160			
Minimum edge distance	c_{min} [mm]	40	50	60	80	-	-	-
	für $s \geq$ [mm]	80	115	140	180			
Uncracked concrete								
Minimum spacing	s_{min} [mm]	40	60	60	80	-	-	-
	für $c \geq$ [mm]	80	140	120	180			
Minimum edge distance	c_{min} [mm]	50	90	75	90	-	-	-
	für $s \geq$ [mm]	100	140	150	200			
Fire exposure from one side								
Minimum spacing	$s_{min,fi}$ [mm]				See normal ambient temperature			
Minimum edge distance	$c_{min,fi}$ [mm]				See normal ambient temperature			
Fire exposure from more than one side								
Minimum spacing	$s_{min,fi}$ [mm]				See normal ambient temperature			
Minimum edge distance	$c_{min,fi}$ [mm]				≥ 300 mm			
Intermediate values by linear interpolation.								
Wedge anchor BZ plus								
Intended use								
Minimum spacings and edge distances for standard anchorage depth								
Annex B4								

Table B3: Minimum spacings and edge distances, reduced anchorage depth, BZ plus

Fastener size		M8	M10	M12	M16
Minimum thickness of concrete member	$h_{\min,3}$ [mm]	80	80	100	140
Cracked concrete					
Minimum spacing	s_{\min} [mm] für $c \geq$ [mm]	50 60	50 100	50 160	65 170
Minimum edge distance	c_{\min} [mm] für $s \geq$ [mm]	40 185	65 180	65 250	100 250
Uncracked concrete					
Minimum spacing	s_{\min} [mm] für $c \geq$ [mm]	50 60	50 100	50 160	65 170
Minimum edge distance	c_{\min} [mm] für $s \geq$ [mm]	40 185	65 180	100 185	170 65
Fire exposure from one side					
Minimum spacing	$s_{\min,fi}$ [mm]		See normal ambient temperature		
Minimum edge distance	$c_{\min,fi}$ [mm]		See normal ambient temperature		
Fire exposure from more than one side					
Minimum spacing	$s_{\min,fi}$ [mm]		See normal ambient temperature		
Minimum edge distance	$c_{\min,fi}$ [mm]		≥ 300 mm		

Intermediate values by linear interpolation.






Wedge anchor BZ plus

Intended use

Minimum spacings and edge distances for reduced anchorage depth

Annex B5

Installation instructions BZ plus

1		Drill hole perpendicular to concrete surface. If using a vacuum drill bit, proceed with step 3.
2		Blow out dust. Alternatively vacuum clean down to the bottom of the hole.
3		Check position of nut.
4		Drive in fastener, such that h_{ef} or $h_{ef,red}$ depth is met. This compliance is ensured, if the thickness of fixture is not greater than the maximum thickness of fixture marked on the fastener in accordance with Annex A3.
5		Installation torque T_{inst} shall be applied by using calibrated torque wrench.

Installation instructions BZ plus with filling of annular gap

1		Drill hole perpendicular to concrete surface. If using a vacuum drill bit, proceed with step 3a.
2		Blow out dust. Alternatively vacuum clean down to the bottom of the hole.
3a		Check position of nut.
3b		Fit the filling washer to the fastener. The thickness of the filling washer must be taken into account with t_{fix} .
4		Drive in fastener with filling washer, such that h_{ref} or $h_{ref,red}$ depth is met. This compliance is ensured, if the thickness of fixture is 5mm smaller than the maximum thickness of fixture marked on the fastener in accordance with Annex A3.
5		Installation torque T_{inst} shall be applied by using calibrated torque wrench.
6		Fill the annular gap between stud and fixture with mortar (compressive strength $\geq 50 \text{ N/mm}^2$ VMH, VMZ or VMU plus). Use enclosed reducing adapter. Observe the processing information of the mortar! The annular gap is completely filled, when excess mortar seeps out.

Wedge anchor BZ plus

Intended Use

Installation instructions with filling washer

Annex B

Table B4: Installation parameters BZ-IG

Fastener size		M6	M8	M10	M12
Effective anchorage depth	h_{ef} [mm]	45	58	65	80
Drill hole diameter	d_0 [mm]	8	10	12	16
Cutting diameter of drill bit	$d_{cut} \leq$ [mm]	8,45	10,45	12,5	16,5
Depth of drill hole	$h_1 \geq$ [mm]	60	75	90	105
Screwing depth of threaded rod	$L_{sd}^{2)} \geq$ [mm]	9	12	15	18
Installation torque, steel zinc plated	S [Nm]	10	30	30	55
	SK [Nm]	10	25	40	50
	B [Nm]	8	25	30	45
Installation torque, stainless steel A4, HCR	S [Nm]	15	40	50	100
	SK [Nm]	12	25	45	60
	B [Nm]	8	25	40	80
Pre-setting installation					
Diameter of clearance hole in the fixture	$d_f \leq$ [mm]	7	9	12	14
Minimum thickness of fixture	S [mm]	1	1	1	1
	SK [mm]	5	7	8	9
	B [mm]	1	1	1	1
Through-setting installation					
Diameter of clearance hole in the fixture	$d_f \leq$ [mm]	9	12	14	18
Minimum thickness of fixture ¹⁾	S [mm]	5	7	8	9
	SK [mm]	9	12	14	16
	B [mm]	5	7	8	9

¹⁾ The minimum thickness of fixture can be reduced to the value of Pre-setting installation, if the shear load at steel failure is designed with lever arm.

²⁾ see Annex A5

Table B5: Minimum spacings and edge distances BZ-IG

Fastener size		M6	M8	M10	M12
Minimum thickness of concrete member	h_{min} [mm]	100	120	130	160
Cracked concrete					
Minimum spacing	s_{min} [mm]	50	60	70	80
	für $c \geq$ [mm]	60	80	100	120
Minimum edge distance	c_{min} [mm]	50	60	70	80
	für $s \geq$ [mm]	75	100	100	120
Uncracked concrete					
Minimum spacing	s_{min} [mm]	50	60	65	80
	für $c \geq$ [mm]	80	100	120	160
Minimum edge distance	c_{min} [mm]	50	60	70	100
	für $s \geq$ [mm]	115	155	170	210
Fire exposure from one side					
Minimum spacing	$s_{min,fi}$ [mm]	See normal temperature			
Minimum edge distance	$c_{min,fi}$ [mm]	See normal temperature			
Fire exposure from more than one side					
Minimum spacing	$s_{min,fi}$ [mm]	See normal temperature			
Minimum edge distance	$c_{min,fi}$ [mm]	≥ 300 mm			

Intermediate values by linear interpolation.

Wedge anchor BZ-IG


Intended use

Installation parameters, minimum spacings and edge distances **BZ-IG**

Annex B8

Installation instructions BZ-IG

Pre-setting installation



Wedge anchor BZ-IG


Intended Use

Installation instructions for pre-setting installation **BZ-IG**

Annex B9

Installation instructions BZ-IG

Through-setting installation



Wedge anchor BZ-IG

Intended Use

Installation instructions for through-setting installation **BZ-IG**

Annex B10

Table C1: Characteristic values for **tension loads**, BZ plus **zinc plated, cracked concrete**, static and quasi-static action

Fastener size		M8	M10	M12	M16	M20	M24	M27
Installation factor	γ_{inst} [-]				1,0			
Steel failure								
Characteristic resistance	$N_{Rk,s}$ [kN]	16	27	40	60	86	126	196
Partial factor	γ_{Ms} [-]	1,53		1,5		1,6	1,5	
Pull-out								
Standard anchorage depth								
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$ [kN]	5	9	16	25	1)	1)	1)
Reduced anchorage depth								
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$ [kN]	5	7,5	1)	1)	-	-	-
Increasing factor for $N_{Rk,p}$	ψ_c [-]	$\left(\frac{f_{ck}}{20}\right)^{0,5}$						
Concrete cone failure								
Effective anchorage depth	h_{ef} [mm]	46	60	70	85	100	115	125
Reduced anchorage depth	$h_{\text{ef,red}}$ [mm]	35 ²⁾	40	50	65	-	-	-
Factor for cracked concrete	$k_1 = k_{cr,N}$ [-]				7,7			

¹⁾ Pull-out is not decisive

²⁾ Use restricted to anchoring of structural components statically indeterminate

Wedge anchor BZ plus

Performance

Characteristic values for **tension loads**, BZ plus **zinc plated, cracked concrete**, static and quasi-static action

Annex C1

Table C2: Characteristic values for **tension loads**, BZ plus **A4 / HCR**,
cracked concrete, static and quasi-static action

Fastener size		M8	M10	M12	M16	M20	M24
Installation factor	γ_{inst} [-]					1,0	
Steel failure							
Characteristic resistance	$N_{Rk,s}$ [kN]	16	27	40	64	108	110
Partial factor	γ_{Ms} [-]			1,5		1,68	1,5
Pull-out							
Standard anchorage depth							
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$ [kN]	5	9	16	25	1)	40
Reduced anchorage depth							
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$ [kN]	5	7,5	1)	1)	-	-
Increasing factor for $N_{Rk,p}$	ψ_c [-]			$\left(\frac{f_{ck}}{20}\right)^{0,5}$			
Concrete cone failure							
Effective anchorage depth	h_{ef} [mm]	46	60	70	85	100	125
Reduced anchorage depth	$h_{\text{ef,red}}$ [mm]	35 2)	40	50	65	-	-
Factor for cracked concrete	$k_1 = k_{cr,N}$ [-]				7,7		

1) Pull-out is not decisive

2) Use restricted to anchoring of structural components statically indeterminate

Wedge anchor BZ plus

Performance

Characteristic values for **tension loads**, BZ plus **A4 / HCR**,
cracked concrete, static and quasi-static action

Annex C2

Table C3: Characteristic values for tension loads, BZ plus zinc plated, uncracked concrete, static and quasi-static action

Fastener size	M8	M10	M12	M16	M20	M24	M27
Installation factor γ_{inst} [-]					1,0		
Steel failure							
Characteristic resistance $N_{Rk,s}$ [kN]	16	27	40	60	86	126	196
Partial factor γ_{Ms} [-]		1,53		1,5	1,6	1,5	
Pull-out							
Standard anchorage depth							
Characteristic resistance in uncracked concrete C20/25 $N_{Rk,p}$ [kN]	12	16	25	35	1)	1)	1)
Reduced anchorage depth							
Characteristic resistance in uncracked concrete C20/25 $N_{Rk,p}$ [kN]	7,5	9	1)	1)	-	-	-
Splitting							
Standard anchorage depth							
Splitting for standard thickness of concrete member (The higher resistance of case 1 and case 2 may be applied; $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$, (Case 2); $\psi_{h,sp}=1,0$)							
Standard thickness of concrete $h_{min,1} \geq$ [mm]	100	120	140	170	200	230	250
Case 1							
Characteristic resistance in uncracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	9	12	20	30	40	62,3	50
Edge distance $c_{cr,sp}$ [mm]					1,5 h_{ref}		
Case 2							
Characteristic resistance in uncracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	12	16	25	35	50,5	62,3	70,6
Edge distance $c_{cr,sp}$ [mm]			2 h_{ref}		2,2 h_{ref}	1,5 h_{ref}	2,5 h_{ref}
Splitting for minimum thickness of concrete member							
Minimum thickness of concrete $h_{min,2} \geq$ [mm]	80	100	120	140			
Characteristic resistance in uncracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	12	16	25	35			
Edge distance $c_{cr,sp}$ [mm]			2,5 h_{ref}				
Reduced anchorage depth							
Minimum thickness of concrete $h_{min,3} \geq$ [mm]	80	80	100	140			
Characteristic resistance in uncracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	7,5	9	17,9	26,5			
Edge distance $c_{cr,sp}$ [mm]	100	100	125	150			
Increasing factor for $N_{Rk,p}$ and $N^0_{Rk,sp}$ ψ_c [-]					$\left(\frac{f_{ck}}{20}\right)^{0,5}$		
Concrete cone failure							
Effective anchorage depth h_{ref} [mm]	46	60	70	85	100	115	125
Reduced anchorage depth $h_{\text{ref,red}}$ [mm]	35 ²⁾	40	50	65	-	-	-
Factor for uncracked concrete $k_1 = k_{ucr,N}$ [-]					11,0		

¹⁾ Pull-out is not decisive

²⁾ Use restricted to anchoring of structural components statically indeterminate

Wedge anchor BZ plus

Performance

Characteristic values for tension loads, BZ plus zinc plated, uncracked concrete, static and quasi-static action

Annex C3

Table C4: Characteristic values for **tension loads**, BZ plus A4 / HCR,
uncracked concrete, static and quasi-static action

Fastener size		M8	M10	M12	M16	M20	M24
Installation factor	γ_{inst}	[-]			1,0		
Steel failure							
Characteristic resistance	$N_{Rk,s}$	[kN]	16	27	40	64	108
Partial factor	γ_{Ms}	[-]		1,5		1,68	1,5
Pull-out							
Standard anchorage depth							
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	25	35	1)
Reduced anchorage depth							
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p}$	[kN]	7,5	9	1)	1)	-
Splitting							
Standard anchorage depth							
Splitting for standard thickness of concrete member (The higher resistance of case 1 and case 2 may be applied; $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$ (Case 2); $\psi_{h,sp}=1,0$)							
Standard thickness of concrete	$h_{min,1} \geq$	[mm]	100	120	140	160	200
Case 1							
Characteristic resistance in uncracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	9	12	20	30	40
Edge distance	$c_{cr,sp}$	[mm]			1,5 h_{ef}		
Case 2							
Characteristic resistance in uncracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	12	16	25	35	50,5
Edge distance	$c_{cr,sp}$	[mm]	115	125	140	200	220
Splitting for minimum thickness of concrete member							
Minimum thickness of concrete	$h_{min,2} \geq$	[mm]	80	100	120	140	
Characteristic resistance in uncracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	12	16	25	35	
Edge distance	$c_{cr,sp}$	[mm]			2,5 h_{ef}		
Reduced anchorage depth							
Minimum thickness of concrete	$h_{min,3} \geq$	[mm]	80	80	100	140	
Characteristic resistance in uncracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	7,5	9	17,9	26,5	
Edge distance	$c_{cr,sp}$	[mm]	100	100	125	150	
Increasing factor for $N_{Rk,p}$ and $N^0_{Rk,sp}$	ψ_c	[-]			$\left(\frac{f_{ck}}{20}\right)^{0,5}$		
Concrete cone failure							
Effective anchorage depth	h_{ef}	[mm]	46	60	70	85	100
Reduced anchorage depth	$h_{ef,red}$	[mm]	35 ²⁾	40	50	65	-
Factor for uncracked concrete	$k_1 = k_{ucr,N}$	[-]			11,0		

¹⁾ Pull-out is not decisive

²⁾ Use restricted to anchoring of structural components statically indeterminate

Wedge anchor BZ plus

Performance

Characteristic values for **tension loads**, BZ plus A4 / HCR,
uncracked concrete, static and quasi-static action

Annex C4

Table C5: Characteristic values for **shear loads**, BZ plus,
cracked and uncracked concrete, static or quasi static action

Fastener size		M8	M10	M12	M16	M20	M24	M27
Installation factor	γ_{inst}	[-]				1,0		
Steel failure without lever arm, Steel zinc plated								
Characteristic resistance	$V^0_{Rk,s}$	[kN]	12,2	20,1	30	55	69	114
Ductility factor	k_7	[-]				1,0		
Partial factor	γ_{Ms}	[-]		1,25			1,33	1,25
Steel failure without lever arm, Stainless steel A4, HCR								
Characteristic resistance	$V^0_{Rk,s}$	[kN]	13	20	30	55	86	123,6
Ductility factor	k_7	[-]				1,0		
Partial factor	γ_{Ms}	[-]		1,25			1,4	1,25
Steel failure with lever arm, Steel zinc plated								
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	23	47	82	216	363	898
Partial factor	γ_{Ms}	[-]		1,25			1,33	1,25
Steel failure with lever arm, Stainless steel A4, HCR								
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	26	52	92	200	454	785,4
Partial factor	γ_{Ms}	[-]		1,25			1,4	1,25
Concrete pry-out failure								
Pry-out factor	k_8	[-]		2,4			2,8	
Concrete edge failure								
Effective length of fastener in shear loading with h_{ef}	Steel zinc plated	l_f	[mm]	46	60	70	85	100
	Stainless steel A4, HCR	l_f	[mm]	46	60	70	85	100
Effective length of fastener in shear loading with $h_{\text{ef,red}}$	Steel zinc plated	$l_{f,\text{red}}$	[mm]	35 ¹⁾	40	50	65	-
	Stainless steel A4, HCR	$l_{f,\text{red}}$	[mm]	35 ¹⁾	40	50	65	-
Outside diameter of fastener	d_{nom}	[mm]		8	10	12	16	20
								24
								27

¹⁾ Use restricted to anchoring of structural components statically indeterminate

Wedge anchor BZ plus

Performance

Characteristic values for **shear loads**, BZ plus,
cracked and uncracked concrete, static or quasi static action

Annex C5

Table C6: Characteristic resistance for **seismic loading**, BZ plus,
standard anchorage depth, performance category **C1** and **C2**

Fastener size	M8	M10	M12	M16	M20
Tension loads					
Installation factor γ_{inst} [-]				1,0	
Steel failure, Steel zinc plated					
Characteristic resistance C1 $N_{Rk,s,\text{eq},C1}$ [kN]	16	27	40	60	86
Characteristic resistance C2 $N_{Rk,s,\text{eq},C2}$ [kN]	16	27	40	60	86
Partial factor γ_{Ms} [-]		1,53		1,5	1,6
Steel failure, Stainless steel A4, HCR					
Characteristic resistance C1 $N_{Rk,s,\text{eq},C1}$ [kN]	16	27	40	64	108
Characteristic resistance C2 $N_{Rk,s,\text{eq},C2}$ [kN]	16	27	40	64	108
Partial factor γ_{Ms} [-]			1,5		1,68
Pull-out (steel zinc plated, stainless steel A4 and HCR)					
Characteristic resistance C1 $N_{Rk,p,\text{eq},C1}$ [kN]	5	9	16	25	36
Characteristic resistance C2 $N_{Rk,p,\text{eq},C2}$ [kN]	2,3	3,6	10,2	13,8	24,4
Shear loads					
Steel failure without lever arm, Steel zinc plated					
Characteristic resistance C1 $V_{Rk,s,\text{eq},C1}$ [kN]	9,3	20	27	44	69
Characteristic resistance C2 $V_{Rk,s,\text{eq},C2}$ [kN]	6,7	14	16,2	35,7	55,2
Partial factor γ_{Ms} [-]		1,25			1,33
Steel failure without lever arm, Stainless steel A4, HCR					
Characteristic resistance C1 $V_{Rk,s,\text{eq},C1}$ [kN]	9,3	20	27	44	69
Characteristic resistance C2 $V_{Rk,s,\text{eq},C2}$ [kN]	6,7	14	16,2	35,7	55,2
Partial factor γ_{Ms} [-]		1,25			1,4
Factor for annular gap	without filling of annular gap α_{gap} [-]			0,5	
	with filling of annular gap α_{gap} [-]			1,0	

Wedge anchor BZ plus

Performance

Characteristic resistance for **seismic loading**, BZ plus,
standard anchorage depth, performance category **C1** and **C2**

Annex C6

Table C7: Characteristic values for tension and shear load under fire exposure, BZ plus, standard anchorage depth, cracked and uncracked concrete C20/25 to C50/60

Fastener size	M8	M10	M12	M16	M20	M24	M27		
Tension load									
Steel failure									
Steel, zinc plated									
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	1,5	2,6	4,1	7,7	9,4	13,6	17,6
	R60		1,1	1,9	3,0	5,6	8,2	11,8	15,3
	R90		0,8	1,4	2,4	4,4	6,9	10,0	13,0
	R120		0,7	1,2	2,2	4,0	6,3	9,1	11,8
Stainless steel A4, HCR									
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	3,8	6,9	12,7	23,7	33,5	48,2	-
	R60		2,9	5,3	9,4	17,6	25,0	35,9	
	R90		2,0	3,6	6,1	11,5	16,4	23,6	
	R120		1,6	2,8	4,5	8,4	12,1	17,4	
Shear load									
Steel failure without lever arm									
Steel, zinc plated									
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	1,6	2,6	4,1	7,7	11	16	20,6
	R60		1,5	2,5	3,6	6,8	11	15	19,8
	R90		1,2	2,1	3,5	6,5	10	15	19,0
	R120		1,0	2,0	3,4	6,4	10	14	18,6
Stainless steel A4, HCR									
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	3,8	6,9	12,7	23,7	33,5	48,2	-
	R60		2,9	5,3	9,4	17,6	25,0	35,9	
	R90		2,0	3,6	6,1	11,5	16,4	23,6	
	R120		1,6	2,8	4,5	8,4	12,1	17,4	
Steel failure with lever arm									
Steel, zinc plated									
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	1,7	3,3	6,4	16,3	29	50	75
	R60		1,6	3,2	5,6	14	28	48	72
	R90		1,2	2,7	5,4	14	27	47	69
	R120		1,1	2,5	5,3	13	26	46	68
Stainless steel A4, HCR									
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	3,8	9,0	19,7	50,1	88,8	153,5	-
	R60		2,9	6,8	14,6	37,2	66,1	114,3	
	R90		2,1	4,7	9,5	24,2	43,4	75,1	
	R120		1,6	3,6	7,0	17,8	32,1	55,5	

If pull-out is not decisive, N_{Rk,p} must be replaced by N⁰_{Rk,c} in equation (D.4) and (D.5), FprEN 1992-4.

Wedge anchor BZ plus

Performance

Characteristic values for tension and shear load under fire exposure, BZ plus, standard anchorage depth, cracked and uncracked concrete C20/25 to C50/60

Annex C7

Table C8: Characteristic values for tension and shear load under fire exposure, BZ plus, reduced anchorage depth, cracked and uncracked concrete C20/25 to C50/60

Fastener size		M8	M10	M12	M16	
Tension load						
Steel failure						
Steel, zinc plated						
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	1,5	2,6	4,1	
	R60		1,1	1,9	3,0	
	R90		0,8	1,3	1,9	
	R120		0,6	1,0	1,3	
Stainless steel A4, HCR						
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	3,2	6,9	12,7	
	R60		2,5	5,3	9,4	
	R90		1,9	3,6	6,1	
	R120		1,6	2,8	4,5	
Shear load						
Steel failure without lever arm						
Steel, zinc plated						
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	1,5	2,6	4,1	
	R60		1,1	1,9	3,0	
	R90		0,8	1,3	1,9	
	R120		0,6	1,0	1,3	
Stainless steel A4, HCR						
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	3,2	6,9	12,7	
	R60		2,5	5,3	9,4	
	R90		1,9	3,6	6,1	
	R120		1,6	2,8	4,5	
Steel failure with lever arm						
Steel, zinc plated						
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	1,5	3,3	6,4	
	R60		1,2	2,5	4,7	
	R90		0,8	1,7	3,0	
	R120		0,6	1,2	2,1	
Stainless steel A4, HCR						
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	3,2	8,9	19,7	
	R60		2,6	6,8	14,6	
	R90		2,0	4,7	9,5	
	R120		1,6	3,6	7,0	
If pull-out is not decisive, N _{Rk,p} must be replaced by N ⁰ _{Rk,c} in equation (D.4) and (D.5), FprEN 1992-4.						
Wedge anchor BZ plus						
Performance Characteristic values for tension and shear load under fire exposure, BZ plus, reduced anchorage depth, cracked and uncracked concrete C20/25 to C50/60						
Annex C8						

Table C9: Displacements under tension load, BZ plus

Fastener size	M8	M10	M12	M16	M20	M24	M27		
Standard anchorage depth									
Steel zinc plated									
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	21,1	24
Displacement	δ_{N0}	[mm]	0,6	1,0	0,4	1,0	0,9	0,7	0,9
	$\delta_{N\infty}$	[mm]	1,4	1,2	1,4	1,3	1,0	1,2	1,4
Tension load in uncracked concrete	N	[kN]	5,7	7,6	11,9	16,7	23,8	29,6	34
Displacement	δ_{N0}	[mm]	0,4	0,5	0,7	0,3	0,4	0,5	0,3
	$\delta_{N\infty}$	[mm]	0,8		1,4	0,8		1,4	
Displacements under seismic tension loads C2									
Displacements for DLS	$\delta_{N,\text{eq}(DLS)}$	[mm]	2,3	4,1	4,9	3,6	5,1	-	-
Displacements for ULS	$\delta_{N,\text{eq}(ULS)}$	[mm]	8,2	13,8	15,7	9,5	15,2	-	-
Stainless steel A4, HCR									
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	19,0	-
Displacement	δ_{N0}	[mm]	0,7	1,8	0,4	0,7	0,9	0,5	-
	$\delta_{N\infty}$	[mm]	1,2	1,4	1,4	1,4	1,0	1,8	-
Tension load in uncracked concrete	N	[kN]	5,8	7,6	11,9	16,7	23,8	33,5	-
Displacement	δ_{N0}	[mm]	0,6	0,5	0,7	0,2	0,4	0,5	-
	$\delta_{N\infty}$	[mm]	1,2	1,0	1,4	0,4	0,8	1,1	-
Displacements under seismic tension loads C2									
Displacements for DLS	$\delta_{N,\text{eq}(DLS)}$	[mm]	2,3	4,1	4,9	3,6	5,1	-	-
Displacements for ULS	$\delta_{N,\text{eq}(ULS)}$	[mm]	8,2	13,8	15,7	9,5	15,2	-	-
Reduced anchorage depth									
Steel zinc plated, stainless steel A4, HCR									
Tension load in cracked concrete	N	[kN]	2,4	3,6	6,1	9,0	-	-	-
Displacement	δ_{N0}	[mm]	0,8	0,7	0,5	1,0	-	-	-
	$\delta_{N\infty}$	[mm]	1,2	1,0	0,8	1,1	-	-	-
Tension load in uncracked concrete	N	[kN]	3,7	4,3	8,5	12,6	-	-	-
Displacement	δ_{N0}	[mm]	0,1	0,2	0,2	0,2	-	-	-
	$\delta_{N\infty}$	[mm]	0,7	0,7	0,7	0,7	-	-	-
Wedge anchor BZ plus									
Performance									
Displacements under tension load									
Annex C9									

Table C10: Displacements under shear load, BZ plus

Fastener size	M8	M10	M12	M16	M20	M24	M27
Standard anchorage depth							
Steel zinc plated							
Shear load in cracked and uncracked concrete	V	[kN]	6,9	11,4	17,1	31,4	36,8
Displacement	δ_{V0}	[mm]	2,0	3,2	3,6	3,5	1,8
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3	2,7
Displacements under seismic shear loads C2							
Displacements for DLS	$\delta_{V,\text{eq}(DLS)}$	[mm]	3,0	2,7	3,5	4,3	4,7
Displacements for ULS	$\delta_{V,\text{eq}(ULS)}$	[mm]	5,9	5,3	9,5	9,6	10,1
Stainless steel A4, HCR							
Shear load in cracked and uncracked concrete	V	[kN]	7,3	11,4	17,1	31,4	43,8
Displacement	δ_{V0}	[mm]	1,9	2,4	4,0	4,3	2,9
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4	4,3
Displacements under seismic shear loads C2							
Displacements for DLS	$\delta_{V,\text{eq}(DLS)}$	[mm]	3,0	2,7	3,5	4,3	4,7
Displacements for ULS	$\delta_{V,\text{eq}(ULS)}$	[mm]	5,9	5,3	9,5	9,6	10,1
Reduced anchorage depth							
Steel zinc plated							
Shear load in cracked and uncracked concrete	V	[kN]	6,9	11,4	17,1	31,4	-
Displacement	δ_{V0}	[mm]	2,0	3,2	3,6	3,5	-
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3	-
Stainless steel A4, HCR							
Shear load in cracked and uncracked concrete	V	[kN]	7,3	11,4	17,1	31,4	-
Displacement	δ_{V0}	[mm]	1,9	2,4	4,0	4,3	-
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4	-
Wedge anchor BZ plus							
Performance							
Displacements under shear load							
Annex C10							

**Table C11: Characteristic values for tension loads, BZ-IG,
cracked concrete, static and quasi-static action**

Fastener size		M6	M8	M10	M12
Installation factor	γ_{inst}	[-]		1,2	
Steel failure					
Characteristic resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0
Partial factor	γ_{Ms}	[-]		1,5	
Characteristic resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8
	γ_{Ms}	[-]		1,87	
Pull-out failure					
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$	[kN]	5	9	12
Increasing factor for $N_{Rk,p}$	ψ_c	[-]		$\left(\frac{f_{ck}}{20}\right)^{0,5}$	
Concrete cone failure					
Effective anchorage depth	h_{ef}	[mm]	45	58	65
Factor for cracked concrete	$k_1 = k_{\text{cr},N}$	[-]		7,7	

Wedge anchor BZ-IG

Performance

Characteristic values for **tension loads, BZ-IG,
cracked concrete**, static and quasi-static action

Annex C11

Table C12: Characteristic values for **tension loads, BZ-IG, uncracked concrete**, static and quasi-static action

Fastener size		M6	M8	M10	M12
Installation factor	γ_{inst}	[-]		1,2	
Steel failure					
Characteristic resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0
Partial factor	γ_{Ms}	[-]		1,5	
Characteristic resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8
Partial factor	γ_{Ms}	[-]		1,87	
Pull-out					
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	20
Splitting (the higher resistance of Case 1 and Case 2 may be applied)					
Minimum thickness of concrete member	h_{\min}	[mm]	100	120	130
Case 1					
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	9	12	16
Edge distance	$c_{cr,sp}$	[mm]		1,5 h_{ef}	
Case 2					
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	12	16	20
Edge distance	$c_{cr,sp}$	[mm]		2,5 h_{ef}	
Increasing factor for $N_{Rk,p}$ and $N_{Rk,sp}^0$	ψ_c	[-]		$\left(\frac{f_{ck}}{20}\right)^{0,5}$	
Concrete cone failure					
Effective anchorage depth	h_{ef}	[mm]	45	58	65
Factor for uncracked concrete	$k_1 = k_{ucr,N}$	[-]		11,0	

Wedge anchor BZ-IG

Performance

Characteristic values for **tension loads, BZ-IG, uncracked concrete**, static and quasi-static action

Annex C12

Table C13: Characteristic values for **shear loads, BZ-IG,**
cracked and uncracked concrete, static and quasi-static action

Fastener size		M6	M8	M10	M12
Installation factor	γ_{inst}	[-]		1,0	
BZ-IG, steel zinc plated					
Steel failure without lever arm, Pre-setting installation					
Characteristic resistance	$V^0_{Rk,s}$	[kN]	5,8	6,9	10,4
Steel failure without lever arm, Through-setting installation					
Characteristic resistance	$V^0_{Rk,s}$	[kN]	5,1	7,6	10,8
Steel failure with lever arm, Pre-setting installation					
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	12,2	30,0	59,8
Steel failure with lever arm, Through-setting installation					
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	36,0	53,2	76,0
Partial factor for $V_{Rk,s}$ and $M^0_{Rk,s}$	γ_{Ms}	[-]		1,25	
Ductility factor	k_7	[-]		1,0	
BZ-IG, stainless steel A4, HCR					
Steel failure without lever arm, Pre-setting installation					
Characteristic resistance	$V^0_{Rk,s}$	[kN]	5,7	9,2	10,6
Partial factor	γ_{Ms}	[-]		1,25	
Steel failure without lever arm, Through-setting installation					
Characteristic resistance	$V^0_{Rk,s}$	[kN]	7,3	7,6	9,7
Partial factor	γ_{Ms}	[-]		1,25	
Steel failure with lever arm, Pre-setting installation					
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	10,7	26,2	52,3
Partial factor	γ_{Ms}	[-]		1,56	
Steel failure with lever arm, Through-setting installation					
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	28,2	44,3	69,9
Partial factor	γ_{Ms}	[-]		1,25	
Ductility factor	k_7	[-]		1,0	
Concrete pry-out failure					
Pry-out factor	k_8	[-]	1,5	1,5	2,0
Concrete edge failure					
Effective length of fastener in shear loading	l_f	[mm]	45	58	65
Effective diameter of fastener	d_{nom}	[mm]	8	10	12
16					

Wedge anchor BZ-IG

Performance

Characteristic values for **shear loads, BZ-IG,**
cracked and uncracked concrete, static and quasi-static action

Annex C13

Table C14: Characteristic values for **tension** and **shear load** under **fire exposure, BZ-IG**, cracked and uncracked concrete C20/25 to C50/60

Fastener size		M6	M8	M10	M12	
Tension load						
Steel failure						
Steel zinc plated						
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	0,7	1,4	2,5	3,7
	R60		0,6	1,2	2,0	2,9
	R90		0,5	0,9	1,5	2,2
	R120		0,4	0,8	1,3	1,8
Stainless steel A4, HCR						
Characteristic resistance	R30	N _{Rk,s,fi} [kN]	2,9	5,4	8,7	12,6
	R60		1,9	3,8	6,3	9,2
	R90		1,0	2,1	3,9	5,7
	R120		0,5	1,3	2,7	4,0
Shear load						
Steel failure without lever arm						
Steel zinc plated						
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	0,7	1,4	2,5	3,7
	R60		0,6	1,2	2,0	2,9
	R90		0,5	0,9	1,5	2,2
	R120		0,4	0,8	1,3	1,8
Stainless steel A4, HCR						
Characteristic resistance	R30	V _{Rk,s,fi} [kN]	2,9	5,4	8,7	12,6
	R60		1,9	3,8	6,3	9,2
	R90		1,0	2,1	3,9	5,7
	R120		0,5	1,3	2,7	4,0
Steel failure with lever arm						
Steel zinc plated						
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	0,5	1,4	3,3	5,7
	R60		0,4	1,2	2,6	4,6
	R90		0,4	0,9	2,0	3,4
	R120		0,3	0,8	1,6	2,8
Stainless steel A4, HCR						
Characteristic resistance	R30	M ⁰ _{Rk,s,fi} [Nm]	2,2	5,5	11,2	19,6
	R60		1,5	3,9	8,1	14,3
	R90		0,7	2,2	5,1	8,9
	R120		0,4	1,3	3,5	6,2

Wedge anchor BZ-IG

Performance

Characteristic values for **tension** and **shear loads** under **fire exposure, BZ-IG**, cracked and uncracked concrete C20/25 to C50/60

Annex C14

Table C15: Displacements under tension load, BZ-IG

Fastener size			M6	M8	M10	M12
Tension load in cracked concrete	N	[kN]	2,0	3,6	4,8	8,0
Displacements	δ_{N0}	[mm]	0,6	0,6	0,8	1,0
	$\delta_{N\infty}$	[mm]	0,8	0,8	1,2	1,4
Tension load in uncracked concrete	N	[kN]	4,8	6,4	8,0	12,0
Displacements	δ_{N0}	[mm]	0,4	0,5	0,7	0,8
	$\delta_{N\infty}$	[mm]	0,8	0,8	1,2	1,4

Table C16: Displacements under shear load, BZ-IG

Fastener size			M6	M8	M10	M12
Shear load in cracked and uncracked concrete	V	[kN]	4,2	5,3	6,2	16,9
Displacements	δ_{V0}	[mm]	2,8	2,9	2,5	3,6
	$\delta_{V\infty}$	[mm]	4,2	4,4	3,8	5,3

Wedge anchor BZ-IG

Performance

Displacements under tension load and under shear load **BZ-IG**

Annex C15